



# ZOFFANY

## EGGSHELL

### DESCRIPTION

Eggshell is a premium quality, traditional alkyd based low sheen finish formulated for interior and exterior use on wood and metal surfaces. It provides a smooth, even surface that is washable and resistant to condensation.

### KEY PROPERTIES

- A traditional solvent-based low sheen finish for interior and exterior. Use on wood and metal.
- Ideal for kitchens, Bathrooms and conservatories
- Resistant to steam and condensation.
- Produces a smooth, washable, hard wearing finish.

### PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Wood or Metal primer. Rub down previously painted surfaces fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

### APPLICATION

Stir well. Easy to apply by brush or roller. Do not apply over polystyrene surfaces.

### CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

### PRECAUTIONS

- FLAMMABLE
- Contains 2-butanone oxime. May produce an allergic reaction.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.

- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.
- Safety data sheet available on request

### RECOMMENDED USES

Suitable for interior and exterior use such as front doors and window frames.

### TYPE OF SUBSTRATE

- Wood and metal.
- Do not use over large surface areas internally.

### COLOUR RANGE

Alchemy of Colour collection, 156 Colours

### FINISH

Low sheen

### VOLUME SOLID

61%

### COVERAGE

Approximately 17 square metres per litre, depending on the nature and porosity of the surface.

### DRYING TIME

Recoat after 16 - 24 hours under normal drying conditions. Touch dry 2 - 3 hours.

### TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

### CLEANER

White spirit

### VOC CONTENT

- High VOC content 25 - 50%
- VOC's (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (Cat A/d): 300g/l (2010). This product contains max 300g/l VOC.

### FILM THICKNESS

Wet: 50µm, dry: 31µm.

### SIZES

1 Litre, 2.5 Litre